



ENDURANCE

SPC FLOORING: UNICLIC / UNIPUSH™ CLICK SYSTEM

UV SURFACE TREATMENT: Thickness In Microns

- Super Stain And Scratch Resistant
- Completely Waterproof
- No Bugs No Termites

TRANSPARENT WEAR LAYER: 0.55 mm

- Enhances the Color And Embossing
- Protects From Abrasion

OVER ALL THICKNESS: 6.50 mm



FILM LAYER: 0.10 mm

- Elegant Wood Designs
- Natural Looking, Natural Feeling

RIGID CORE: 4.35 mm

- Sturdy Construction
- Dimensional Stability
- UNICLIC™ / UNIPUSH™ Click System
- Quick And Easy Installation

IXPE Backing: 1.50 mm

- 1.50 mm IXPE Backing With Good Grip
- Insulates Sound
- Provides Underfoot Comfort

FEATURES & BENEFITS



Superior Scratch & Stain Resistant



No Bugs & Termites



Click Installation
No Adhesive



100%
Waterproof



Easy
Clean



Multiple Color
Combinations



Natural Looking
Design



Zero
Maintenance



Superb
Dimensional
Stability



Endures
Medium
Foot Traffic



Excellent
Sound
Insulation



No Sub-Floor
Required



Corporate Offices



Residential



Retail



Hospitality



SPC FLOORING: UNICLIC / UNIPUSH™ CLICK SYSTEM

SPC FLOORING FOR HEAVY COMMERCIAL USE | PUR Polyurethane Reinforcement | Product Standard **ENDURANCE** ASTM F3261-17

CERTIFICATION & CLASSIFICATION	STANDARD	ENDURANCE SERIES
TYPE OF FLOOR COVERING	ASTM F3261 EN 16511	RESILIENT FLOORING IN MODULAR FORMAT WITH RIGID CORE (SPC)
CE CERTIFICATION	EN 14041	YES
CLASSIFICATION	EN ISO 10874	HEAVY TRAFFIC : CLASS 34

TECHNICAL CHARACTERISTICS	STANDARDS	ENDURANCE SERIES
TOTAL THICKNESS	EN ISO 24336 (EN 428)	6.50 MM
WEAR LAYER THICKNESS	EN ISO 24340 (EN 429)	22 MIL WL 0.55 MM
SURFACE TREATMENT	UV TREATED	PUR
TOTAL WEIGHT	EN ISO 23997 (EN 430)	2.13 LBS / SQ FT = 10.40 KG / m ²
WEAR LAYER BINDER CONTENT	ISO 10582	TYPE I
FORM OF DELIVERY	EN ISO 24342 (EN 427) PLANKS IN CARTON	7" X 60" = 23.88 SF / CARTON
		182 mm X 1524 mm = 2.22 m ² / CARTON
	PIECES	8 PIECES PER CARTON
	EDGE FINISH	PAINTED BEVEL

TECHNICAL PERFORMANCES	STANDARDS	ENDURANCE SERIES
DIMENSIONAL STABILITY	EN ISO 23999 (EN 434)	< 0.10%
REACTION TO FIRE	EN 13501 – 1	BFL-S1 PASS
RESIDUAL INDENTATION	EN ISO 24343-1 (EN 433)	REQUIRED VALUE : < 0.10 MM AVERAGE MEASURED VALUE : 0.03 MM
FURNITURE LEG	EN 424	NO DAMAGE
CASTOR CHAIR	EN ISO 4918 (EN 425)	NO DAMAGE
CURL RESULTANT TO HEAT	EN ISO 23999 (434)	< 2MM PASS
IMPACT SOUND REDUCTION	EN ISO 140-8 EN ISO 717/2	Δ LNw = 21 DB
LIGHT FASTNESS	EN ISO 105 – B02	PASS
RESISTANCE TO CHEMICALS	EN ISO 26987 (EN423)	GOOD RESISTANCE PASS
SLIP RESISTANCE	DIN51130 EN 13893	R9 PASS
STATIC LOAD	ASTM F970 / F387	PASS



ISO 9001
ISO 14001
ISO 18001



EN 14041

